

L Number	Hits	Search Text	DB	Time stamp
-	2	("6348705").PN.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:11
-	13687	@ad<=20010508 and 'high dielectric constant'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:31
-	132	(@ad<=20010508 and 'high dielectric constant') and 'conductive barrier'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:24
-	119	((@ad<=20010508 and 'high dielectric constant') and 'conductive barrier') and Al	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:24
-	77	((@ad<=20010508 and 'high dielectric constant') and 'conductive barrier') and Aluminum	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:25
-	3291	@ad<=20010508 and 'BST'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:33
-	79	(@ad<=20010508 and 'BST') and 'TiAlN'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:34
-	39	((@ad<=20010508 and 'BST') and 'TiAlN') and aluminum	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 08:34
-	6626	((257/295-296) or (257/751) or (257/310) or (438/3) or (257/763-764) or (257/303) or (257/306)).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 11:37
-	24	((((257/295-296) or (257/751) or (257/310) or (438/3) or (257/763-764) or (257/303) or (257/306)).CCLS.) and @ad<=20010508 and 'BST' and 'TiAlN' and 'metal layer'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 12:52
-	29173	@ad<=20010508 and 'ferroelectric'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 12:05
-	30	(@ad<=20010508 and 'ferroelectric') and 'BST' and 'TiAlN' and 'metal layer'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 14:56
-	29	(@ad<=20010508 and 'ferroelectric') and 'BST' and 'TiAlN' and 'aluminum'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 13:26
-	20	(@ad<=20010508 and 'ferroelectric') and 'capacitor' with 'BST' and 'TiAlN' and 'aluminum'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 13:26

-	25	@ad<=20010508 and 'perovskite BST' or 'amorphous BST'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 15:09
-	3	@ad<=20010508 and 'amorphous BST' and conductive adj barrier	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 15:40
-	569	(257/310).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 15:41
-	532	((257/310).CCLS.) and @ad<=20010508	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 15:51
-	11	(@ad<=20010508 and 'ferroelectric') and 'BST' and 'barrier' and 'aluminum layer'	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2002/09/16 15:45